

クオリティ160AS UV3G (A.B.C) 在庫

仕様

| | |
|-------|---|
| 材質 | 高屈折率プラスチックレンズ |
| 基準径 | マイナス(Φ75) プラス(Φ75・Φ70・Φ65) |
| 屈折率 | 1.60 |
| 比重 | 1.34 |
| アッベ数 | 37 |
| コート | ABC+Z コート(ブルーライトカット+硬化+ 超撥水+帯電防止コート) |
| 視感透過率 | 95% |
| 紫外線 | UV3G |
| 設計 | 非球面設計 |

■在庫度数範囲表
(略号:G60BZ)

| 乱視(-) | | | | 球面 数 (-) | 球面 数 (+) | 乱視(+) | | | | |
|-------|------|------|------|----------------|----------------|-------|------|------|------|--|
| 2.00 | 1.75 | 1.50 | 1.25 | | | 2.00 | 1.75 | 1.50 | 1.25 | |
| | | | | 0.00 | | | | | | |
| | | | | 25 | | | | | | |
| | | | | 50 | | | | | | |
| | | | | 75 | | | | | | |
| | | | | 1.00 | | | | | | |
| | | | | 25 | | | | | | |
| | | | | 50 | | | | | | |
| | | | | 75 | | | | | | |
| | | | | 2.00 | | | | | | |
| | | | | 25 | | | | | | |
| | | | | 50 | | | | | | |
| | | | | 75 | | | | | | |
| | | | | 3.00 | | | | | | |
| | | | | 25 | | | | | | |
| | | | | 50 | | | | | | |
| | | | | 75 | | | | | | |
| | | | | 4.00 | | | | | | |
| | | | | 25 | | | | | | |
| | | | | 50 | | | | | | |
| | | | | 75 | | | | | | |
| | | | | 5.00 | | | | | | |
| | | | | 25 | | | | | | |
| | | | | 50 | | | | | | |
| | | | | 75 | | | | | | |
| | | | | 6.00 | | | | | | |

| MIX 範囲 | | | | |
|--------|------|------|------|------|
| C(-) | 0 | 1 | 2 | |
| S(+) | 0.50 | 0.75 | 1.00 | 1.25 |
| | 0.25 | | | |
| | 50 | | | |
| | 75 | | | |
| | 1.00 | | | |
| | 25 | | | |
| | 50 | | | |
| | 75 | | | |

在庫度数範囲