

プレミアム174DAS Zコート (略号：R74Z)

仕様

材質	超高屈折率プラスチックレンズ
基準径	マイナス (Φ75・Φ70・Φ65)
屈折率	1.74
比重	1.47
アッベ数	33
コート	Z コート (硬化コート+超撥水)
視感透過率	98%
紫外線	UV400加工
設計	両面非球面設計

特殊加工 (有料)

染色	アリアーテトレス (下記カラー濃度は染色不可) フェア***/グロウ***/トゥルー***/ブリーズ*** それぞれ50F、50G、50/20の濃度 コパー85F/スモーク85F/フォレスト85F エクストラファイン不可 見本色不可
----	--

※外径指定、厚み指定、プリズム加工等の特注加工はお受けできません。

■製作度数範囲表

乱視 (-)										球面 度数
4.00	3.75	3.50	3.25	3.00	2.75	2.50	2.25	2.00	1.75	
										0.00
										25
										50
										75
										1.00
										25
										50
										75
										2.00
										25
										50
										75
										3.00
										25
										50
										75
										4.00
										25
										50
										75
										5.00
										25
										50
										75
										6.00
										25
										50
										75
										7.00
										25
										50
										75
										8.00
										25
										50
										75
										9.00
										25
										50
										75
										10.00
										50
										11.00
										50
										12.00
										50
										13.00
										50
										14.00
										50
										15.00

75

70

65

在庫度数範囲